

basic information	brand	Aumark
	sub-brand	Aumark TX-T
	brand in market	Aumark TX-T
	model	BJ5049V8BDA-2
	model number	5049V8BDA-02DA03
	product platform	2.0T
body	model	L1800
	type	Single row seat tilttable
Whole vehicle main dimensions	Overall dimensions (LxWxH)mm	xx
	chassis dimensions (LxWxH)mm	5875×1915×2230
	Inner dimensions of the cargo body (LxWxH)mm	xx
	Wheel track (front/rear) (mm)	1530/1485
	Wheel base (mm)	3360
Weight data	Rated payload (kg)	3000
	Persons in cab (persons)	2
Whole vehicle main performance	Max. speed (km/h)	95
	Max. slope of climb (%)	30
	Fuel consumption (L/100km)	10
	Min. turning diameter (m)	10.6
	min. ground clearance (mm)	180
Engine	model	BJ493ZLQV1(VE PUMP)
	Type	Four-cylinder, in-line, turbocharging,Four-stroke,intercooling,
	Displacement (L)	2.771
	Rated power (kw/rpm)	80/3600
	Max torque (N.m/rpm)	280/1900~2300
	emission stadard	EURO.III
	supplier	FOTON
ClutchGearbox	Gearbox Model	JC5-28
	Speed ratio	I:4.717 II:2.513 III:1.679 IV:1.000 V:0.784 R:4.497
	PTO/PTO Connector	PTO Connector
	Supplier	jiangchi
	cluth model	φ260×φ160
	PTO	x
chassis main performance	Front axle Model	Forging h-beam
	Rated load (T)	2.2
	Rear axle Model	monolithic construction
	Rated load (T)	5T
	gear ratio	6.142
	Tyre model	7.00R16
	Quantity	6+1
	Steering gear	Circular ball type
	Type	Power steering
	Front suspension	non-independent suspension
	Leaf spring number	3+1
	Rear suspension	non-independent suspension
	Leaf spring number	6+7
	Fuel tank material	AL
	Cubage (L) :	120
Brake system	Service brake	drum type pneumatic braking
	Parking brake	Centra drum brake
	Auxiliary brake	Exhaust brake
	loading sensing pressure propoportoining valve	•
Electrical system	Rated voltage (V) :	12
	Battery	100Ah
Product configuration	Heater	•
	Adjustable steering wheel	•
	Electric flameout	•
	double sun shield	•
	battery cover	•
	radio	•
MP3 :	•	